



Synflex HP Air/Nitrox Hoses – Hire

As well as being a supplier of new Synflex hoses, we also have a large hire fleet of readymade tested/cleaned hoses of various lengths and sizes ready for dispatch at short notice.

For further details please contact us at sales@searchwise.co.uk



Nominal I.D.	Maximum O.D.		Minimum Bend Radius		Recommended Working Pressure @ Safety Factor		Minimum Burst Pressure		Weight		Swage Die Part No. 4540	Permanent Coupling Series* Steel	Reusable Coupling Series* Steel	
	in	mm	in	mm	4:1	3:1	psi	bar	100 ft	100 m				
3/16	4.8	.515	13.1	1-1/2	38	5,000	460	20,000	1,379	7.7	11.5	H03	390H/790H	390J
1/4	6.4	.625	15.9	2	51	5,000	460	20,000	1,379	11.8	17.6	H04	390H/790H	390J
3/8	9.5	.765	19.4	2-1/2	64	4,000	368	16,000	1,103	14.8	22.0	H06	390H/790H	390J
1/2	12.7	.892	22.7	4	102	3,500	322	14,000	965	19.0	28.3	H08	390H/790H	390J
3/4	19.1	1.138	28.9	6-1/2	165	2,250	207	9,000	620	25.6	38.1	H12	390H/790H	390J
1	25.4	1.468	37.3	10	254	2,000	184	8,000	552	38.5	57.3	H16	390H	390J